



**ENERG**  
енергия · ενεργεια



**NIBE**

NIBE F1255-16



55 °C

35 °C



**A++**

**A++**



**42** dB



dB

■ 16  
■ **16**  
■ 16  
kW

■ 16  
■ **16**  
■ 16  
kW



2015

811/2013



**ENERG**  
енергия · ενέργεια


Y IJA  
IE IA

**NIBE**



NIBE F1255-16



**A++**



**A**



2015

811/2013



# ENERG

енергия · ενέργεια

Y






IJA


IE


IA


**NIBE**


## NIBE F1255-16













+ 

+ 

+ 

+ 









## Product fiche

Supplier's name:	<b>NIBE</b>		
Model:	<b>NIBE F1255-16</b>		
Temperature application	<b>35</b>	<b>55</b>	°C
Declared load profile for water heating	<b>XL</b>		
Seasonal space heating energy efficiency class, average climate:	<b>A++</b>	<b>A++</b>	
Water heating energy efficiency class, average climate:	<b>A</b>		
Rated heat output, average climate:	16	16	kW
Annual energy consumption for space heating, average climate	6373	8167	kWh
Annual electricity consumption for water heating, average climate	1709		kWh
Seasonal space heating energy efficiency, average climate:	199	154	%
Water heating energy efficiency, average climate:	98		%
Sound power level LWA indoors	42	42	dB
Rated heat output, cold climate:	16	16	kW
Rated heat output, warm climate:	16	16	kW
Annual energy consumption for space heating, cold climate	7218	9434	kWh
Annual electricity consumption for water heating, cold climate	1709		kWh
Annual energy consumption for space heating, warm climate	4169	5386	kWh
Annual electricity consumption for water heating, warm climate	1709		kWh
Seasonal space heating energy efficiency, cold climate:	211	159	%
Water heating energy efficiency, cold climate:	98		%
Seasonal space heating energy efficiency, warm climate:	197	151	%
Water heating energy efficiency, warm climate:	98		%
Sound power level LWA outdoors	-	-	dB

## Data for package fiche

Controller class	VI		
Controller contribution to efficiency	4		%
Seasonal space heating energy efficiency of package, average climate:	203	158	%
Seasonal space heating energy efficiency class for package, average climate:	<b>A+++</b>	<b>A+++</b>	%
Seasonal space heating energy efficiency of package, cold climate:	215	163	%
Seasonal space heating energy efficiency of package, warm climate:	201	155	%

<b>Model(s):</b>		<b>NIBE F1255-16</b>							
Type of heat source/sink:		Brine-to-water							
Low-temperature heat pump:		No							
Equipped with supplementary heater:		Yes							
Heat pump combination heater:		Yes							
Climate condition:		Average							
Temperature application:		Medium temperature (55 °C)							
Applied standards: EN14825 and EN16147									
<b>Rated heat output</b>		Prated	16,0	kW	<b>Seasonal space heating energy efficiency</b>		$\eta_s$	154	%
<i>Declared capacity for part load at outdoor temperature Tj</i>				<i>Declared coefficient of performance for part load at outdoor temperature Tj</i>					
Tj = -7 °C	Pdh	14,2	kW	Tj = -7 °C	COPd	3,0	-		
Tj = +2 °C	Pdh	8,7	kW	Tj = +2 °C	COPd	4,1	-		
Tj = +7 °C	Pdh	5,6	kW	Tj = +7 °C	COPd	4,9	-		
Tj = +12 °C	Pdh	5,5	kW	Tj = +12 °C	COPd	5,0	-		
Tj = biv	Pdh	15,4	kW	Tj = biv	COPd	2,8	-		
Tj = TOL	Pdh	15,4	kW	Tj = TOL	COPd	2,8	-		
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		-		
Bivalent temperature				T <sub>biv</sub>	-10	°C	Operation limit temperature		
Cycling interval capacity for heating				P <sub>cyh</sub>		kW	Cycling interval efficiency		
Degradation co-efficient				Cdh	0,99	-	Heating water operating limit		
<i>Power consumption in modes other than active mode</i>				<i>Supplementary heater</i>					
Off mode	P <sub>OFF</sub>	0,002	kW	Rated heat output		P <sub>sup</sub>	0,6	kW	
Thermostat-off mode	P <sub>TO</sub>	0,02	kW						
Standby mode	P <sub>SB</sub>	0,007	kW	Type of energy input		Electric			
Crankcase heater mode	P <sub>CK</sub>	0,03	kW						
<i>Other items</i>									
Capacity control		variable		Rated air flow rate, outdoors					m <sup>3</sup> /h
Sound power level, indoors/outdoors		L <sub>WA</sub>	42/-	dB					
Annual energy consumption		Q <sub>HE</sub>	8167	kWh	Rated brine or water flow rate, outdoor heat exchanger			1,84	m <sup>3</sup> /h
<i>For heat pump combination heater:</i>									
<b>Declared load profile</b>		<b>XL</b>		<b>Water heating energy efficiency</b>		$\eta_{wh}$	98	%	
Daily electricity consumption		Q <sub>elec</sub>	7,78	kWh	Daily fuel consumption		Q <sub>fuel</sub>		kWh
Annual electricity consumption		AEC	1709	kWh	Annual fuel consumption		AFC		GJ
<b>Approved by:</b>									
<b>Contact details</b>		© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden							